

Architecture

Physical	Dimensions	Width: 2.125 in. (54 mm) Length: 3.375 in. (85.7 mm)
Type	Shelf Manager	Mezzanine module to mount to a management carrier or an ATCA module

Standards

Module Management	IPMI	IPMI Version 2.0 and PICMG 3.x
-------------------	------	--------------------------------

Configuration

Power	VT001	2.2W.
	Temperature	Operating Temperature: 0° to 65° C (Available in Industrial Temp) Storage Temperature: -40° to +90° C
Environmental	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
Mechanical	Interface Connectors	Tyco/Samtec 120 pin
Software	Operating Systems	Linux version 2.6.15 with VadaTech Shelf and/or Node management as application

Other

MTBF	MIL Spec 217-F > 257,000 Hrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.