

Architecture

| | | |
|----------|---------------|---|
| Physical | Dimensions | Width: 2.125 in. (54 mm) Length: 3.375 in. (85.7 mm) |
| Type | Shelf Manager | Mezzanine module to mount to a management carrier or an ATCA module |

Standards

| | | |
|-------------------|------|--------------------------------|
| Module Management | IPMI | IPMI Version 2.0 and PICMG 3.x |
|-------------------|------|--------------------------------|

Configuration

| | | |
|---------------|----------------------|--|
| Power | VT002 | 3W. |
| | Temperature | Operating Temperature: 0° to 65° C (Available in Industrial Temp) Storage Temperature: -40° to +90° C |
| Environmental | Vibration | 1G, 5-500Hz each axis |
| | Shock | 30Gs each axis |
| Mechanical | Relative Humidity | 5 to 95 percent, non-condensing |
| Software | Interface Connectors | Tyco/Samtec 120 pin |
| | Operating Systems | Linux version 2.6.21 with VadaTech Shelf and/or Node management as application |

Other

| | |
|----------------------|---|
| MTBF | MIL Spec 217-F > 242,000 Hrs. |
| Certifications | Designed to meet FCC, CE and UL certifications where applicable |
| Standards | VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards |
| Compliance | RoHS and NEBS |
| Warranty | Two (2) years |
| Trademarks and Logos | The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice. |