

Specifications

Architecture	
Physical	Dimensions Width: 2.125" (54 mm) Depth 3.375" (85.7 mm)
Type	Shelf Manager Mezzanine module to mount to a management carrier or an ATCA module
Standards	
Module Management	IPMI IPMI v2.0 and PICMG 3.0
Configuration	
Power	VT003 3W
Environmental	Temperature See Ordering Options Storage Temperature: -40° to +90°C
	Vibration Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock Operating 30G each axis
	Relative Humidity 5 to 95% non-condensing
Others	Mechanical Tyco/Samtec 120 pin
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty	Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.