

Shelf Manager for LCR ATCA Chassis – VT004

SPECIFICATIONS

Architecture		
Physical	Dimensions	Width: 3.937" (100 mm) Depth: 11.06" (280.7 mm)
Type	Shelf Manager	For LCR Chassis: 14 and 5 slot
Standards		
Module Management	IPMI	IPMI version 2.0 and PICMG 3.0
Configuration		
Power	VT004	4 W typical, 5 W max
Environmental	Temperature	Operating Temperature: 0° to 55° C, (Air flow requirement is to be greater than 100 LFM) Available in Industrial Temp Storage Temperature: -40° to +90° C
	Vibration	1G, 5 – 500 Hz on each axis
	Shock	30Gs on each axis
	Relative Humidity	5 to 95 percent, non-condensing
Front Panel	Interface Connectors	Micro DB-15 connector for telco alarm RS-232 via Micro DB-9 10/100 Ethernet via RJ-45
	LEDs	IPMI Management Activity/Link and User LEDs
	Push Button	Reset switch
	Mechanical	Hot-swap extractor handle
Software	Operating Systems	Linux
Other		
MTBF	MIL Hand book 217-F @ 233,000 Hrs	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Compliance	RoHS and NEBS	
Warranty	Two (2) years	
Trademarks and Disclaimer	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice	