

Architecture		
Physical	Dimensions	Width:5.687 in. (144 mm) Depth:11.077 in. (281 mm)
Type	Shelf Manager	For Kaparal chassis; 14 and 5 slot
Standards		
Module Management	IPMI	IPMI Version 2.0 and PICMG 3.0
Configuration		
Power	VT004 Temperature	4W typical, 5W max. Operating Temperature: 0° to 65° C (Air flow requirement is to be greater than 100 LFM) Available in Industrial Temp Storage Temperature: -40° to +90° C
Environmental	Vibration Shock	1G, 5-500Hz each axis 30Gs each axis
Front Panel	Relative Humidity	5 to 95 percent, non-condensing
	Interface Connectors	DB15 connector for Telco alarm RS-232 via RJ-45
		10/100 Ethernet RJ-45 Reset Switch
	LEDs	IPMI Management Control Activity/Link; user LED, etc.
Software Support	Push Button	Reset Switch
	Mechanical Operating Systems	Hot Swap Ejector Handle Linux version 2.6.15
Other		
MTBF	MIL Spec 217-F > 225,000 Hrs.	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Compliance	RoHS and NEBS	
Warranty	Two (2) years	
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved, Specification subject to change without notice.	