

Specifications

Architecture		
Physical	Dimensions	Width: 5.685" (144 mm)
		Depth 7.0" (177.8 mm)
Type	Shelf Manager	Stand-Alone (Bench-top)
Standards		
Module Management	IPMI	IPMI v2.0 and PICMG 3.0
Configuration		
Power	VT007	3W
Environmental	Temperature	See Ordering Options
		Storage Temperature: -40° to +90°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock	Operating 30G each axis
Front	Interface Connectors	Debug Port, RS-232
		Dual 10/100 Ethernet RJ-45
		Modem Interface DB25
	Push Button	Reset Switch
	LEDs	IPMI management control Activity/Link user LEDs
Rear	Interface Connectors	DB15 for Telco Alarm
		DB15 with x5 I ² C busses
		Input power 12V
Software Support	Operating System	Linux v2.6.15
Other		
MTBF	MIL Hand book 217-F@ TBD hrs	
Certifications	Designed to meet FCC, CE and UL certifications, where applicable	
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards	
Warranty	Two (2) years, see VadaTech Terms and Conditions	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.