

Architecture

Physical	Dimensions	Width:3.937 in. (100 mm) Depth:11.06 in. (280.7 mm)
Type	Shelf Manager	Manages up to 18 Blades

Standards

Module Management	IPMI	IPMI Version 2.0 and PICMG 3.0
-------------------	------	--------------------------------

Configuration

Power	VT009	5W typical, 5.5W max.
	Temperature	Operating Temperature: 0° to 65° C (Air flow requirement is to be greater than 100 LFM) Available in Industrial Temp Storage Temperature: -40° to +90° C
Environmental	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
Front Panel	Interface Connectors	RS-232 via RJ-45 10/100 Ethernet RJ-45
	LEDs	IPMI Management Control Activity/Link; user LED, etc.
	Push Button	Reset Switch
	Mechanical	Hot Swap Ejector Handle
Software Support	Operating Systems	Linux version 2.6.21

Other

MTBF	MIL Spec 217-F > TBD Hrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.