

## Architecture

Physical	Dimensions	Width: 5.685 in. (144 mm) Depth: 11.096 in. (281 mm)
Type	Shelf Manager	For Intel compatible chassis

## Standards

Module Management	IPMI	IPMI Version 2.0 and PICMG 3.0
-------------------	------	--------------------------------

## Configuration

Power	VT004	4W typical, 5W max
	Temperature	Operating Temperature: 0° to 65° C (Air flow requirement is to be greater than 100 LFM) Available in Industrial Temp Storage Temperature: -40° to +90° C
Environmental	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
Front Panel		DB15 connector for Telco alarm
	Interface Connectors	RS-232 via RJ-45 Dual 10/100 Ethernet RJ-45 Reset Switch
	LEDs	IPMI Management Control Activity/Link; user LED, etc.
	Push Button	Reset Switch
Software Support	Mechanical	Hot Swap Ejector Handle
	Operating Systems	Linux version 2.6.15

## Other

MTBF	MIL Spec 217-F > 220,000 Hrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.