

Architecture		
Physical	Dimensions	Width: 3.07 in. (78 mm) Depth: 11.466 in. (291 mm)
Type	Shelf Manager	For ELMA chassis
Standards		
Module Management	IPMI	IPMI Version 2.0 and PICMG 3.0
Configuration		
Power	VT004	4W typical, 5W max
Environmental	Temperature	Operating Temperature: 0° to 65° C (Air flow requirement is to be greater than 100 LFM) Available in Industrial Temp Storage Temperature: -40° to +90° C
	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
Front Panel	Relative Humidity	5 to 95 percent, non-condensing
	Interface	DB15 connector for Telco alarm
	Connectors	RS-232 via Micro DB-9 10/100 Ethernet via RJ-45
	Reset Switch	Reset Switch Alarm Clear
Software Support	LEDs	IPMI Management Control Activity/Link; user LED, etc.
	Push Button	Reset Switch and Telco Alarm Clear
	Mechanical	Hot Swap Ejector Handle
Operating Systems		Linux version 2.6.15
Other		
MTBF		MIL Handbook 217-F > 220,000 Hrs.
Certifications		Designed to meet FCC, CE and UL certifications where applicable
Standards Compliance		VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards RoHS and NEBS
Warranty		Two (2) years
Trademarks and Logos		The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMCTM and the AdvancedTCATM logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.