

# Specifications

Architecture	
<b>Physical</b>	<b>Dimensions</b> Width: 3.07" (78 mm)
	Depth 11.46" (291 mm)
<b>Type</b>	<b>Shelf Manager</b> For VadaTech VT834 ATCA Chassis
Standards	
<b>ATCA</b>	<b>Type</b> PICMG 3.0 Revision 2.0
<b>Module Management</b>	<b>IPMI</b> IPMI v2.0
Configuration	
<b>Power</b>	<b>VT036</b> 7W
<b>Environmental</b>	<b>Temperature</b> See <a href="#">Ordering Options</a>
	Storage Temperature: -40° to +85°C
	<b>Vibration</b> Operating 9.8 m/s <sup>2</sup> (1G), 5 to 500 Hz on each axis
	<b>Shock</b> Operating 30G each axis
	<b>Relative Humidity</b> 5 to 95% non-condensing
<b>Front Panel</b>	<b>Interface Connectors</b> DB15 connector for Telco Alarm
	DB9 for CPU RS-232
	RJ-45 for 10/100
	Micro USB for IPMI RS-232
	Single 10/100 out of band port support to the shelf manager
	RJ-45 x4 for Ethernet
	<b>LEDs</b> IPMI management, Activity and Status
	<b>Push Button</b> Telco Alarm reset and system reset
<b>Software Support</b>	<b>Operating System</b> N/A
Other	
<b>MTBF</b>	MIL Hand book 217-F@ TBD hrs
<b>Certifications</b>	Designed to meet FCC, CE and UL certifications, where applicable
<b>Standards</b>	VadaTech is certified to both the ISO9001:2015 and AS9100D standards
<b>Warranty</b>	Two (2) years, see <a href="#">VadaTech Terms and Conditions</a>

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.