

Specifications

Architecture		
Physical	Dimensions	Width: 3.07" (78 mm)
		Depth: 11.46" (291 mm)
		Height 3HP
Type	Shelf Manager	For VadaTech VT835 ATCA Chassis
Standards		
ATCA	Type	PICMG 3.0 Revision 2.0
Module Management	IPMI	Version 2.0
Configuration		
Power	VT037	5W
Environmental	Temperature	Operating temperature: -5° to 45° C (55°C for limited time, performance restrictions may apply), industrial and extended versions also available (See environmental spec sheet)
		Storage Temperature: -40° to +85°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500Hz on each axis
	Shock	Operating 30Gs on each axis
Front Panel	Interface Connectors	DB-15 for Telco Alarm
		DB9 for CPU RS-232
		RJ-45 for 10/100
		Micro USB for IPMI RS-232
	Push buttons for Reset and Telco Alarm clear	
	LEDs	IPMI, Activity and Status
Software Support	Operating System	N/A
Conformal Coating		Humiseal 1A33 Polyurethane (Optional)
		Humiseal 1B31 Acrylic (Optional)
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty		Two (2) years

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of ATCA and μ TCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTM), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.

Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.