

Specifications

Architecture	
Physical	Dimensions Width: 2.125" (54 mm) Length: 3.08" (78.2 mm)
Type	System Manager Mezzanine module to mount to a management carrier within the chassis
Standards	
Module Management	IPMI IPMI v2.0, VITA 65 and VITA 46.11
Configuration	
Power	VT042R ~2W
Environmental	Temperature See Ordering Options Operating Temperature: -40° to +85°C Storage Temperature: -55° to +100°C
	Vibration Follows the VITA spec (see ordering option)
	Shock Follows the VITA spec (see ordering option)
	Relative Humidity 5 to 95% non-condensing
Others	Mechanical Tyco/Samtec 60 pin
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty	Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.