

Specifications

Architecture	
Physical	Dimensions Width: 5.685" (144 mm)
	Depth 11.096" (281 mm)
Type	Shelf Manager VadaTech ATCA Shelf Manager
Standards	
Module Management	IPMI IPMI v2.0 and PICMG 3.0
Configuration	
Power	VT052 TBD W
Environmental	Temperature See Ordering Options
	Storage Temperature: -40° to +90°C
	Vibration Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock Operating 30G each axis
	Relative Humidity 5 to 95% non-condensing
Front Panel	Interface Connectors Micro DB15 connector for Telco Alarm
	RJ-45 for RS-232 port
	Single 10/100 out of band port support to the shelf manager
	Quad GbE ports (10/100/1000) and dual SFP+
	LEDs IPMI management control
	Activity/Link user LEDs
	Mechanical Hot-swap ejector handle
Cap-screw	
	Push Button Alarm reset and system reset
Software Support	Operating System Linux (consult factory for VxWorks, Windows, or other options)
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty	Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.