

Specifications

Architecture		
Physical	Dimensions	Width: x" (x mm)
		Length: y" (y mm)
Type	Backplane	Single slot
Standards		
AMC	PICMG	AMC.0
Configuration		
Power	VT074	16-38V DC, up to 120W for the AMC module
Environmental	Temperature	See Ordering Options
		Storage Temperature: -40° to +90°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock	Operating 30G each axis
	Relative Humidity	5 to 95% non-condensing
Rear of the Chassis	Interface Connectors	x2 RJ-45 for GbE
		QSFP+
		OCuLink
	LEDs	LNK/ACT for GbE
		Payload power
Other		
MTBF	MIL Hand book 217-F@ TBD hrs	
Certifications	Designed to meet FCC, CE and UL certifications, where applicable	
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards	
Warranty	Two (2) years, see VadaTech Terms and Conditions	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.