

Architecture		
Physical	Dimensions	Width: 19 in. (482.6 mm) Depth: 27.6 in. (700 mm)
Type	PMC Carrier	Up to 16 PrPMC/PMC slots
Standards		
PMC	Type	IEEE1386
PTMC	Type	PICMG TDMA routed on J4 Connector
Module Management	IPMI	IPMI Version 2.0
Configuration		
Power	VT802	10W typical without any PrPMC/PMCs modules loaded (20W max with all the GbE at line rate)
Rear I/O	Interface Connectors	RS-232 IPMI management Debug port RJ-45 style Ethernet 10/100 IPMI management out of band port Power Input 24 RJ-45 pass-throughs
Front Panel	Interface Connectors	Dual 10/100/1000-BaseT for uplink from the GbE switch fabric Option for front panel SC style fiber connector
Environmental	Temperature	Operating Temperature: 0° to 55° C Storage Temperature: -40° to +90° C
	Relative Humidity	5 to 95 percent, non-condensing
Other		
MTBF	MIL Spec 217-F >168,000 Hrs.(not including the Fan)	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Compliance	RoHS	
Warranty	Two (2) years	
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. All rights reserved. Specification subject to change without notice.	