

VT086

Advanced Secure Keyboard, Video and Mouse (KVM) Receiver



VT086

Key Features

- VT086 in conjunction with the VT085 form a complete secure remote KVM over fiber (VT086 is the receiver side)
- USB 2.0 encoded over Fiber with USB white listing for secure USB devices
- USB Hub for additional devices
- DP++, DP (Display Port) or HDMI over Fiber
- Capable of video overlay at the output
- Lossless video encode/decode
- Utilizing LC style Fiber (single TX/RX)
- Glass to glass latency of less than 20ms
- Rugged Connectors
- Encrypted package over Fiber for secure communication between the receiver and transmitter
- Ethernet and Serial port for configuration and management
- Secure Key capable

Benefits

- VadaTech 3rd Generation KVM
- Compact size with low (15W) power consumption
- Electrical, mechanical, software, and system-level expertise in house
- Full system supply from industry leader
- AS9100 and ISO9001 certified company



vadatech
THE POWER OF VISION



VT086

VT086, when used in conjunction with a VT085, forms a complete KVM extension over a secure LC Fiber link. Data is encoded using a proprietary algorithm which, together with the use of fiber, combats interception of sensitive data.

The VT086 decodes the USB2.0 over Fiber as well as dual DP++, Display Port (DP) or HDMI. A USB hub is included to support up to 5 external Ports. The video can be up to 4K resolution on each of the two video outputs. The output video has capability for overlay and the overlay images are programmable and controlled over Ethernet by the user. Video encode/decode is lossless.

The VT086 has a GbE (10/100/1000) Port for the management of the overlays, command and configuration, etc.

The VT085/VT086 encoding/decoding and data processing is done in hardware for a very low latency protocol. The glass to glass latency is less than 20ms.

The module supports white listing of attached USB devices. The host USB can only numerate approved devices, preventing unauthorized access. It can also store a secure key to ensure the unit cannot be compromised.

The module utilizes ruggedize I/O connectors for harsh environments.

The VT086 is orderable with a fanless enclosure or optionally as a board-level product without enclosure. This allows customers to fully integrate the unit into their own user compute/server environment.



Figure 1: VT086

Block Diagram




Figure 2: VT086 Functional Block Diagram



Figure 3: Conduction cool deployment example

VT085/VT086 Connectivity




Figure 3: VT085/VT086 Connectivity Block Diagram

Specifications

Architecture		
Physical	Dimensions	Width: 5.89" (149.6 mm) bare module without the enclosure
		Depth 4.43" (112.5 mm) bare module without enclosure
Type	KVM	KVM over Fiber (receiver side)
Standards		
Module Management	IPMI	IPMI v2.0 and PICMG 3.0 and VITA
Configuration		
Power	VT086	15W (+5V Input)
Environmental	Temperature	See Ordering Options
		Storage Temperature: -40° to +90°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock	Operating 30G each axis
	Relative Humidity	5 to 95% non-condensing
Others	Mechanical	Conduction cool with enclosure
Other		
MTBF	MIL Hand book 217-F@ TBD hrs	
Certifications	Designed to meet FCC, CE and UL certifications, where applicable	
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards	
Warranty	Two (2) years, see VadaTech Terms and Conditions	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.

Ordering Options

VT086 – ABC-000-0HJ

A = Video Input*		
0 = DP++ 1 = DP** 2 = HDMI**		
B = Enclosure		H = Temperature Range
0 = No Enclosure 1 = Enclosure with Fan 2 = Enclosure Fan less		1 = Commercial (-5° to 55°C) 2 = Industrial (-20° to 65°C) 3 = Extended (-40° to 75°C)
C = Input Power Adapter		J = Conformal Coating
0 = No Input Power Adapter 1 = +5V AC Adapter		0 = No coating 1 = Humiseal 1A33 Polyurethane 2 = Humiseal 1B31 Acrylic

Notes:

*Both Video Inputs must be identical.

**Minimum order qty required.

Related Products

ATC128



- Dual socket 24-core Intel® Xeon® Platinum Processors - Scalable Performance (SP)
- Multiple SKU support (i.e. 8256, 8253, 6238T, 6230T, 5220T, 5218T, 4209T, etc.)
- Twelve banks of DDR4 for up to 384 GB with ECC per socket (total of 768 GB)

ATC342



- AdvancedTCA Video Mixer (Windowing)
- External Input: 4 Analog and 1 DVI-I (Analog or 24-bit Digital)
- External Output: Analog daisy-chain and 1 DVI-I (Analog and 24-bit Digital)

VT835



- 19" rack mount 3U ATCA Hybrid AMC Chassis
- 1x ATCA slot, 8 mid-size AMC slots and 2x ATCA RTM slots
- 40G or 10G fabric across the backplane

Contact

VadaTech Corporate Office

198 N. Gibson Road, Henderson, NV 89014

Phone: +1 702 896-3337 | Fax: +1 702 896-0332

Asia Pacific Sales Office

7 Floor, No. 2, Wenhua Street, Neihu District, Taipei 114, Taiwan

Phone: +886-2-2627-7655 | Fax: +886-2-2627-7792

VadaTech European Sales Office

VadaTech House, Bulls Copse Road, Southampton, SO40 9LR

Phone: +44 2380 016403

info@vadatech.com | www.vadatech.com

Choose VadaTech

We are technology leaders

- First-to-market silicon
- Constant innovation
- Open systems expertise

We commit to our customers

- Partnerships power innovation
- Collaborative approach
- Mutual success

We deliver complexity

- Complete signal chain
- System management
- Configurable solutions

We manufacture in-house

- Agile production
- Accelerated deployment
- AS9100 accredited



Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

© 2020 VadaTech Incorporated. All rights reserved.

DOC NO. 4FM737-12 REV 01 | VERSION 1.3 – AUG/21

