

Architecture

Physical	Dimensions	Width: 2.2 in. (55.88 mm)
		Depth: 1.95 in. (49.53 mm)
Type	IPMI FAN Controller	Intelligent fan controller for ATCA-style chassis

Standards

Module Management	IPMI	IPMI Version 2.0 and PICMG 3.0
-------------------	------	--------------------------------

Configuration

Power	VT098	< 1W
	Temperature	Operating Temperature: 0° to 65° C, Available in Industrial Temp Storage Temperature: -40° to +90° C
Environmental	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
Features	Relative Humidity	5 to 95 percent, non-condensing
	External interface	2x15 0.1 Terminal Strip
	LEDs	IPMI Management Control Blue, Red, Amber and Green
	Switch	Hot swap switch input with +/-15KV ESD protection
	Zones	Three Zone with six TACH inputs
	Temp Sensor	Two temp sensors on-board

Other

MTBF	MIL Spec 217-F > 432,000 Hrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years
Trademarks	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.