

## SPECIFICATIONS

Architecture		
Physical	Dimensions	Height 8U
		Width 19"
		Depth 14.9" without handles and 16.23" with handles
Type	μTCA Chassis	Twelve mid-size AMC.0 double module slots
Standards		
AMC	Type	AMC.1, AMC.2, AMC.3 and AMC.4
μTCA	Type	Telco Alarm, Dual MCH, Quad Power Module and Dual Intelligent Cooling units
Configuration		
Power	VT811	1000W redundant AC, 110V - 240V AC with frequency from 47 - 63 Hz
Environmental	Temperature	Operating Temperature: 0° to 55° C
		Storage Temperature: -40° to +70° C
	Altitude	10,000 ft operating
		40,000 ft non-operating
Relative Humidity	5 to 95 percent, non-condensing	
Conformal Coating	Humiseal 1A33 Polyurethane (Optional)	
	Humiseal 1B31 Acrylic (Optional)	
Other		
MTBF	MIL Hand book 217-F @ TBD Hrs	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	Two (2) years	
Trademarks and Disclaimer	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice	

## REAR VIEW

