

Specifications

Architecture		
Physical	Dimensions	Width: 19"
		Depth: 14.2"
		Height: 1U
		Weight 8 lbs
Type	MTCA Chassis	Two MTCA.4 Slots with Micro RTMs Telco Alarm, JSM, integrated GbE, Single Power Module and Intelligent Cooling Unit
Standards		
AMC	Type	AMC.0, AMC.1, AMC.2, AMC.3 and AMC.4
MTCA	Type	PICMG 3.0 Rev 3.0
Configuration		
Power	VT819	400W AC, 85-265V AC with frequency from 47-63 Hz
		400W DC, -36 to -75V DC
Environmental	Temperature	See Ordering Options Storage Temperature: -40° to +85°C
	Altitude	10, 000 ft operating
		40, 000 ft non-operating
	Relative Humidity	5 to 95% non-condensing
Cooling		Right to Left
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty		One (1) year, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.