

Specifications

Architecture	
Physical	Dimensions Height: 6U Width: 19" Depth: 13" (handles protrude and additional 2" out the front of the shelf)
Type	ATCA Shelf 6 Slot ATCA Payload
Standards	
ATCA	Type PICMG 3.0 Rev 3.0
Configuration	
Power	VT837 3x swappable 1300W AC or 2x 90 Amp DC Power Entry Modules 100 to 240V AC or -36 to -72V DC
Environmental	Temperature See Ordering Options Storage Temperature: -40° to +70°C Relative Humidity 5 to 95% non-condensing
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty	One (1) year, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.