

Specifications

| Architecture | |
|-----------------------|---|
| Physical | Dimensions Height: 1U Width: 19" Depth: 18.5" |
| Type | MTCA Chassis 6 AMC slots |
| Standards | |
| AMC | Type AMC.1, AMC.2 and AMC.3 |
| MTCA | Type MicroTCA.0 |
| Configuration | |
| Power | VT840 300W Universal AC or 398W DC (-36V to -75V) @ 400 Hz |
| Environmental | Temperature See Ordering Options Storage Temperature: -40° to +70°C |
| | Altitude 10,000 ft operating 40,000 ft non-operating |
| | Relative Humidity 5 to 95% non-condensing |
| Other | |
| MTBF | MIL Hand book 217-F@ TBD hrs |
| Certifications | Designed to meet FCC, CE and UL certifications, where applicable |
| Standards | VadaTech is certified to both the ISO9001:2015 and AS9100D standards |
| Warranty | One (1) year, see VadaTech Terms and Conditions |

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.