

Architecture

Physical	Dimensions	Height 5U
		Width: 19" Depth 10.25" without the handles and 12" with the handles
Type	µTCA Chassis	Twelve AMC.0 slots

Standards

AMC	Type	AMC.0, AMC.1, AMC.2, AMC.3, and AMC.4
µTCA	Type	JSM, Telco Alarm, Dual MCH, Dual Power Module and Dual Intelligent Cooling units

Configuratrion

Power	VT860	1000W supply 110-240VAC with frequency from 47-63Hz
	Temperature	Operating Temperature: 0° to 55° C Storage Temperature: -40° to +70° C
Environmental	Altitude	10,000 ft. Operating 40,000 ft. Non-Operating
	Relative Humidity	5 to 95 percent, non-condensing
Conformal Coating		Humiseal 1A33 Polyurethane Humiseal 1B31 Acrylic

Other

MTBF	MIL Hand book 217-F@ TBD Hrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

