

Physical	Dimensions	Height 5U Width: 19" Depth 10.25" without the handles and 12" with the handles
Type	μTCA Chassis	10 AMC.0 full-size slots
Standards		
AMC	Type	AMC.0, AMC.1, AMC.2, AMC.3, and AMC.4
μTCA	Type	Telco Alarm, Dual MCH, Dual Power Module and Dual Intelligent Cooling units
Configuration		
Power	VT862	1000W supply 110-240VAC with frequency from 47-63Hz
	Temperature	Operating Temperature: 0° to 55° C Storage Temperature: -40° to +70° C
Environmental	Altitude	10,000 ft. Operating 40,000 ft. Non-Operating
Conformal Coating	Relative Humidity	5 to 95 percent, non-condensing Humiseal 1A33 Polyurethane Humiseal 1B31 Acrylic
Other		
MTBF	MIL Hand book 217-F@ TBD Hrs.	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Compliance	RoHS and NEBS	
Warranty	Two (2) years	
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.	

