

Architecture

Physical	Dimensions	Height 5U Width: 19" Depth 10.25" without the handles and 12" with the handles
Type	µTCA Chassis	10 AMC.0 full-size slots
Standards		
AMC	Type	AMC.0, AMC.1, AMC.2, AMC.3, and AMC.4
µTCA	Type	Telco Alarm, Dual MCH, Dual Power Module and Dual Intelligent Cooling units
Configuration		
Power	VT864	1000W supply 110-240VAC with frequency from 47-63Hz
Environmental	Temperature	Operating Temperature: 0° to 55° C Storage Temperature: -40° to +70° C
	Altitude	10,000 ft. Operating 40,000 ft. Non-Operating
	Relative Humidity	5 to 95 percent, non-condensing
Conformal Coating		Humiseal 1A33 Polyurethane Humiseal 1B31 Acrylic
Other		
MTBF		MIL Hand book 217-F@ TBD Hrs.
Certifications		Designed to meet FCC, CE and UL certifications where applicable
Standards		VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance		RoHS and NEBS
Warranty		Two (2) years
Trademarks and Logos		The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCATM and the AdvancedMCTM logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

