

Architecture

Physical	Dimensions	Height 214mm
		Width:124mm Depth 248mm (without the cables)
Type	µTCA Chassis	8 AMC.0 slots

Standards

AMC	Type	AMC.0, AMC.1, AMC.2, AMC.3, and AMC.4
µTCA	Type	Telco Alarm, Single MCH, Power Module and SFM (System Management Module)

Configuration

Power	VT875	Single PM (consult UTC011 data sheet for the power module)
	Temperature	Operating Temperature: -40° to 80° C Storage Temperature: -45° to +95° C
Environmental	Vibration	TBD
	Shock	TBD
	Altitude	15,000 ft. Operating with no external Fan with 105W dissipation 40,000 ft. Non-Operating
Conformal Coating	Relative Humidity	5 to 95 percent, non-condensing
		Humiseal 1A33 Polyurethane Humiseal 1B31 Acrylic

Other

MTBF	MIL Hand book 217-F@ TBD Hrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

