

VT878 – Compact μ TCA Conduction Cooled Chassis, 2 AMCs

SPECIFICATIONS

Architecture		
Physical	Dimensions	Height 1"
		Width 10.5"
		Depth 9.0"
		Weight: 2 kg (typical)
Type	μ TCA Chassis	2 AMC.0 mid-size, single module slots
Standards		
AMC	Type	AMC.0, AMC.1, AMC.2, AMC.3 and AMC.4
μ TCA	Type	μ TCA.3 without clamshell
Configuration		
Power	VT878	12 VDC standard input, other available on request
Environmental	Temperature	Contact VadaTech (Installed Module Dependent)
		Storage Temperature: -40° to $+90^{\circ}$ C
	Vibration	Contact VadaTech
	Shock	30G on each axis
	Relative Humidity	5 to 95 percent, non-condensing
Other		
MTBF	MIL Hand book 217-F @ TBD Hrs	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Compliance	RoHS and NEBS	
Warranty	Two (2) years	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of ATCA and μ TCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTM), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information

Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.