

Specifications

Architecture	
Physical	Dimensions Height: 2U Width: 19" Depth: 14.2"
Type	MTCA Chassis 12 AMC.0 Slots
Standards	
AMC	Type AMC.0, AMC.1, AMC.2, AMC.3 and AMC.4
MTCA	Type JSM, Telco Alarm, Dual MCH, Dual Power Module and Dual Intelligent Cooling units
Configuration	
Power	VT886 Dual Power Module (PM) Inserted from the rear 800W Universal AC Input (110-240V AC with frequency from 47-63 Hz) per Module
Environmental	Temperature See Ordering Options Storage Temperature: -40° to +70°C
	Altitude 10,000 ft operating 40,000 ft non-operating
	Relative Humidity 5 to 95% non-condensing
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty	One (1) year, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.