

7U μ TCA Chassis, 12 AMC Slots, Bottom-to-Top Cooling – VT892

SPECIFICATIONS

Architecture		
Physical	Dimensions	Height: 7U
		Width: 19"
		Depth: 10.25" without handles and 12" with the handles
Type	μ TCA Chassis	12 Full-size, double module AMC slots
		Telco Alarm, JSM, Dual MCH, Dual Power Module and Dual Intelligent Cooling Units
Standards		
AMC	Type	AMC.0, AMC.1, AMC.2, AMC.3 and AMC.4
μ TCA	Type	PICMG 3.0 Rev 3.0
Configuration		
Power	VT892	1000 W supply
		110-240 VAC with frequency from 47-63Hz
Environmental	Temperature	Operating Temperature: 0° to 55° C
		Storage Temperature: -40° to +70° C
	Altitude	10,000 ft operating
		40,000 ft non-operating
Relative Humidity	5 to 95 percent, non-condensing	
Conformal Coating		Humiseal 1A33 Polyurethane (Optional)
		Humiseal 1B31 Acrylic (Optional)
Other		
MTBF		MIL Hand book 217-F @ TBD Hrs
Certifications		Designed to meet FCC, CE and UL certifications where applicable
Standards		VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty		Two (2) years
Trademarks and Disclaimer		The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice

CHASSIS CONFIGURATION

