

# Specifications

Architecture	
<b>Physical</b>	<b>Dimensions</b> Width: 19" Depth: 8.35" Height: 3U
<b>Type</b>	<b>MTCA Chassis</b> 12 AMC.0 single module, (6 mid-size and 6 full size)
Standards	
<b>AMC</b>	<b>Type</b> AMC.0, AMC.1, AMC.2, AMC.3 and AMC.4
<b>MTCA</b>	<b>Type</b> MicroTCA.1
Configuration	
<b>Power</b>	<b>VT930</b> Dependent on Power Module used
<b>Environmental</b>	<b>Temperature</b> Operating temperature: -20° to +70° C Storage Temperature: -40° to +70°C
	<b>Altitude</b> 10,000 ft operating 40,000 ft non-operating
	<b>Relative Humidity</b> 5 to 95% non-condensing
Other	
<b>MTBF</b>	MIL Hand book 217-F@ TBD hrs
<b>Certifications</b>	Designed to meet FCC, CE and UL certifications, where applicable
<b>Standards</b>	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
<b>Warranty</b>	One (1) year, see <a href="#">VadaTech Terms and Conditions</a>

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.