

Specifications

Architecture	
Physical	Dimensions Height: 6U Width: 19" Depth 13.64" deep (without handles and connectors)
Type	MTCA Chassis 12 AMC.0: 8 Mid-size and 4 Full-size slots or 10 Full-size
Standards	
AMC	Type AMC.0, AMC.1, AMC.2, AMC.3 and AMC.4
MTCA	Type PICMG 3.0 Rev 2.0
Module Management	IPMI v2.0
Configuration	
Power	VT969 Power Module dependent DC Input from 18-36V, 10-36V or -36 to -75V (Power Module dependent)
Environmental	Temperature See Ordering Options Storage Temperature: -40° to +85°C Altitude 10,000 ft operating 40,000 ft non-operating Vibration 8G random operating (contact Sales for other requirements) Shock 20G/11ms operating (contact Sales for other requirements) Relative Humidity 5 to 95% non-condensing
Front Panel	Interface Connectors Contact Sales LEDs Power and Activity/Fault/Ready
Software Support	Operating System Agnostic
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty	Two (2) year, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.