

Specifications

Architecture		
Physical	Dimensions	Width: 12"
		Depth: 9.84"
		Height: 2"
Type	Chassis	ADC/DAC Data Acquisition
Configuration		
Power	VT983	~90W
Environmental	Temperature	See Ordering Options
		Storage Temperature: -40° to +90°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500Hz on each axis
	Shock	Operating 325G/2 ms, 160G/1 ms
	Relative Humidity	5 to 95% non-condensing
Rear Panel	Interface Connectors	AC Mains inlet (universal input)
		POAG ID6
		2x SFP+ for 10GbE or other protocols
		2x RJ-45 for GbE
		1x USB 3.0 and 1x USB 2.0
		HDMI, Display Port
		RS-232 vis Micro USB
Software Support	Operating System	Linux
Other		
MTBF	MIL Hand book 217-F@ TBD hrs	
Certifications	Designed to meet FCC, CE and UL certifications, where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	One (1) year, see VadaTech Terms and Conditions	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.