

# Specifications

Architecture		
Physical	Dimensions	Width: 19"
		Depth: 4"
Type	Rackmount	IBERT Testing Module
Standards		
VPX	Type	OpenVPX
Configuration		
Power	VT985	Application dependent
Environmental	Temperature	Operating temperature: -5° to 55°C
		Storage Temperature: -40° to +85°C
	Vibration	Operating 9.8 m/s <sup>2</sup> (1G), 5 to 500 Hz on each axis
	Shock	Operating 30G on each axis
	Relative Humidity	5 to 95% non-condensing
Front Panel	Interface Connectors	2 x 60-pin high density connectors
		3 x 96-pin high density connectors
		4 x SMA connectors
	Switches	Power toggle and 2x push button
	LEDs	Power failure status
Software Support	Mechanical	Power switch
		Operating System
Other		
MTBF	MIL Hand book 217-F@ TBD hrs	
Certifications	Designed to meet FCC, CE and UL certifications, where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	One (1) year, see <a href="#">VadaTech Terms and Conditions</a>	

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.