

SPECIFICATIONS

Architecture

Physical	Dimensions	Single or double module Height: 2 HP Depth: 7.11 in. (180.6 mm) for single or double module
Type	Filler Panel	To prevent air flow through the front of the chassis

Standards

μTCA	Type	μTCA.0, μTCA.1/4
-------------	------	------------------

Configuration

Power	VT993	0 W
Environmental	Temperature	Operating temperature: -50° to 85° C Storage Temperature: -70° to +95° C

Other

MTBF	MIL Hand book 217-F @ TBD Hrs
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty	Two (2) years

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of ATCA and μTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTM), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information

Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.