

Specifications

Architecture	
Physical	Dimensions 6U VPX backplane
Type	Backplane P0/P1/P2/etc. (option for VITA66.5 and VITA 67.2) as well as RP0/RP1/PR2/etc.
Standards	
VPX	Type VITA46.x
VPX	Type VITA 65 OpenVPX
Configuration	
Power	Provided by the lugs for +12V/+5V/+3.3_AUX/+12V_AUX/-12V_AUX
I/O	Interface Connector Toggle switches for GA (Geographic Address); I2C break out for the IPMC; clocks; etc. JTAG
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty	Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of VPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.