

# Specifications

Architecture		
Physical	Dimensions	Height: 2U
		Width: 19"
		Depth: 12.5"
		Weight: TBD
Type	VPX	3 Payload Slot up to 1.0" pitch
Standards		
VPX	Type	VITA 46.0 Baseline Specification
Configuration		
Power	VTX881	800W/1200W Universal AC Input or -48V DC 650W/1200W
Environmental		See <a href="#">Ordering Options</a>
Cooling		Right to left
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty		One (1) year, see <a href="#">VadaTech Terms and Conditions</a>

OpenVPX allows for a wide range of pin assignments and use cases. Prior to purchasing VadaTech products as standalone items (i.e., not part of an integrated platform) please consult with VadaTech on the system architecture to ensure compatibility.

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.