

AMC312

5 Port USB 1.1 to Fiber Media Converter



AMC312

Key Features

- 5 Channel USB 1.1 Copper to Fiber Converter
- I/O connectivity for Copper is via DP style connector
- I/O connectivity for Fiber is via MTP/MPO style cable
- AMC.0 specification
- IPMI 2.0 compliant
- RoHS compliant

Benefits

- Extends USB connection beyond 5m limit
- Uses standard fiber type for ease of deployment
- Design utilizes proven VadaTech subcomponents and engineering techniques
- Electrical, mechanical, software, and system-level expertise in house
- Full system supply from industry leader
- AS9100 and ISO9001 certified company

AdvancedMC™



vadatech
THE POWER OF VISION



AMC312


The AMC312 is a single module, mid-size (full-size option available) AdvancedMC (AMC) five USB 1.1 Copper to Fiber converter.

The module extends the USB 1.1 length beyond the 5 meter which is specified by the specification. The module allows a seamless connection between the root complex and the end point device.

The module does not take any power from the host USB ports.



Block Diagram



Specifications

Architecture		
Physical	Dimensions	Single module, mid-size (full-size optional) Width: 2.89" (73.5 mm) Depth 7.11" (180.6 mm)
Type	AMC Serial USB 1.1	5 ports copper to fiber converter
Standards		
AMC	Type	AMC.0
Module Management	IPMI	IPMI version 2.0
USB		5 ports USB 1.1
Configuration		
Power	AMC312	10 W
Environmental	Temperature	Operating temperature: -5° to 45° C (55°C for limited time, performance restrictions may apply), industrial and extended versions also available (See environmental spec sheet) Storage Temperature: -40° to +85°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500Hz on each axis
	Shock	Operating 30G on each axis
	Relative Humidity	5 to 95 per cent, non-condensing
Front Panel	Interface Connectors	Mini Display Port for copper MTP/MPO connector for fiber Micro USB for IPMI RS-232
	LEDs	IPMI management control Status
	Mechanical	Hot swap ejector handle
Software Support	Operating System	Independent
Conformal Coating		Humiseal 1A33 Polyurethane (Optional) Humiseal 1B31 Acrylic (Optional)
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty		Two (2) years

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of ATCA and μ TCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTM), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.

Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

Ordering Options

AMC312 – 00C-000-00J

C = Front Panel		J = Temperature Range and Coating
1 = Reserved 2 = Mid-size 3 = Full-size		0 = Commercial, No coating 1 = Commercial, Humiseal 1A33 polyurethane 2 = Commercial, Humiseal 1B31 acrylic 3 = Industrial, No coating 4 = Industrial, Humiseal 1A33 polyurethane 5 = Industrial, Humiseal 1B31 acrylic 6 = Extended, Humiseal 1A33 polyurethane 7 = Extended, Humiseal 1B31 acrylic

Related Products

UTC004



- Single module, full size per AMC.0
- Unified 1GHz quad-core CPU for MCMC (MicroTCA Carrier Management Controller), Shelf Manager, Clocking, and Fabric management
- Automatic fail-over with redundant UTC004s

VT081



- Supports USB 1.1 over fiber
- Fits into any assembly
- Four USB copper ports

VT866



- μ TCA System Platform 19" x 5U x 10.5" deep (with handles 12" deep)
- Full redundancy with dual MicroTCA Carrier Hub (MCH), dual Cooling Units and dual Power Modules
- Up to 12 AMCs in single width/full-size

Contact

VadaTech Corporate Office

198 N. Gibson Road, Henderson, NV 89014

Phone: +1 702 896-3337 | Fax: +1 702 896-0332

Asia Pacific Sales Office

7 Floor, No. 2, Wenhua Street, Neihu District, Taipei 114, Taiwan

Phone: +886-2-2627-7655 | Fax: +886-2-2627-7792

VadaTech European Sales Office

VadaTech House, Bulls Copse Road, Southampton, SO40 9LR

Phone: +44 2380 016403

info@vadatech.com | www.vadatech.com

Choose VadaTech

We are technology leaders

- First-to-market silicon
- Constant innovation
- Open systems expertise

We commit to our customers

- Partnerships power innovation
- Collaborative approach
- Mutual success

We deliver complexity

- Complete signal chain
- System management
- Configurable solutions

We manufacture in-house

- Agile production
- Accelerated deployment
- AS9100 accredited



vadatech
THE POWER OF VISION

Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

© 2017 VadaTech Incorporated, All rights reserved.
DOC NO. 4FM737-12 REV 01 | VERSION 1.1 – JUL17