

# VPX029

3U VPX Power Module DC Input  
600W



VPX029

## Key Features

- Power Module for Open VPX VITA 62
- 3U VPX Systems
- 600W Output Power
- 2KVdc input to output functional isolation
- Input voltage +36V to +75V (nominal +48V)
- Available in Conduction Cooled
- Meets Mil-STD-704F, MIL-STD-461G, MIL-STD-810G
- Health Management through dedicated Processor

## Benefits

- Most comprehensive VPX products in the market
- Electrical, mechanical, software, and system-level expertise in house
- Full system supply from industry leader
- AS9100 and ISO9001 certified company



**vadatech**  
THE POWER OF VISION

**OpenVPX**™



# VPX029

The VPX029 is a power module per VITA 62. The VPX029 is designed for 3U VPX systems and provides +12V, +12V\_AUX and +3.3V\_AUX to the backplane.

The module has dedicated health management per VITA46.11 and interfaces to the backplane using dual IPMI buses. The module has ENABLE, INHBIT, FAIL, Geographic address, and SYSRESET connections to the backplane.

The module is designed to meet the following MIL-STDs:

- MIL-STD-704F
- MIL-STD-461G
- MIL-STD-810G



Figure 1: VPX029



Figure 2: VPX029 Top View



Figure 3: VPX029 Front View

## Block Diagram




Figure 4: VPX029 Functional Block Diagram

# Specifications

Architecture		
<b>Physical</b>	<b>Dimensions</b>	3U, 1" pitch
Standards		
<b>VPX</b>	<b>Type</b>	VITA 46.0
<b>VPX</b>	<b>Type</b>	VITA 65 OpenVPX
<b>Module Management</b>	<b>IPMI</b>	IPMI v2.0
Configuration		
<b>Power</b>	<b>VPX029</b>	Power Entry Module with 36-75V input 600W 2KVdc Isolation
<b>Front Panel</b>	<b>Micro USB</b>	RS-232 for Health Management
	<b>LEDs</b>	User defined by Health Management
<b>Onboard Interfaces</b>		Dual IPMI Buses
<b>VPX Interfaces</b>	<b>Slot Profiles</b>	See <a href="#">Ordering Options</a>
	<b>Rear IO</b>	Per VITA62 (Fail, Inhibit, Geographic address, etc.)
	<b>Backplane</b>	Connector per VITA 62
Other		
<b>MTBF</b>	MIL Hand book 217-F@ TBD hrs	
<b>Certifications</b>	Designed to meet FCC, CE and UL certifications, where applicable	
<b>Standards</b>	VadaTech is certified to both the ISO9001:2015 and AS9100D standards	
<b>Warranty</b>	Two (2) years, see <a href="#">VadaTech Terms and Conditions</a>	

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.

# Ordering Options

## VPX029\* – 000-000-GHJ

		<b>G = Applicable Slot Profile</b>
		0 = 5 HP, VITA 48.1 1 = Reserved
		<b>H = Environmental</b>
		See <a href="#">Environmental Specification</a>
		<b>J = Conformal Coating</b>
		0 = No coating 1 = Humiseal 1A33 Polyurethane 2 = Humiseal 1B31 Acrylic

### Notes:

\*Per VITA specification +5V, +3.3V and -12V is required. The VPX029 provides only +12V, +12V\_AUX and +3.3V+\_AUX to the backplane.

## Environmental Specification

Air Cooled			Conduction Cooled		
Option H	H = 0	H = 1	H = 2	H = 3	H = 4
Operating Temperature	AC1* (0°C to +55°C)	AC3* (-40°C to +70°C)	CC1* (0°C to +55°C)	CC3* (-40°C to +70°C)	CC4* (-40°C to +85°C)
Storage Temperature	C1* (-40°C to +85°C)	C3* (-50°C to +100°C)	C1* (-40°C to +85°C)	C3* (-50°C to +100°C)	C3* (-50°C to +100°C)
Operating Vibration	V2* (0.04 g2/Hz max)	V2* (0.04 g2/Hz max)	V3* (0.1 g2/Hz max)	V3* (0.1 g2/Hz max)	V3 (0.1 g2/Hz max)
Storage Vibration	OS1* (20g)	OS1* (20g)	OS2* (40g)	OS2* (40g)	OS2* (40g)
Humidity	95% non-condensing	95% non-condensing	95% non-condensing	95% non-condensing	95% non-condensing

### Notes:

\*Nomenclature per ANSI/VITA 47. Contact local sales office for conduction cooled (H = 2, 3, 4).

## Related Products

VPX516



- 3U FPGA carrier for FPGA Mezzanine Card (FMC) per VITA 46 and VITA 57
- Xilinx Virtex-7 690T FPGA in FFG-1761 package
- High-performance clock jitter cleaner

VPX592



- 3U FPGA carrier for FMC per VITA 46 and VITA 57
- Xilinx Kintex UltraScale™ XCKU115 FPGA
- High-performance clock jitter cleaner

VPX599



- Xilinx Kintex UltraScale™ XCKU115 FPGA
- Dual ADC 12-bit @ 6.4 GSPS
- Dual DAC 16-bit @ 12 GSPS (AD9162 or AD9164)

# Contact

## VadaTech Corporate Office

198 N. Gibson Road, Henderson, NV 89014

Phone: +1 702 896-3337 | Fax: +1 702 896-0332

## Asia Pacific Sales Office

7 Floor, No. 2, Wenhui Street, Neihu District, Taipei 114, Taiwan

Phone: +886-2-2627-7655 | Fax: +886-2-2627-7792

## VadaTech European Sales Office

VadaTech House, Bulls Copse Road, Southampton, SO40 9LR

Phone: +44 2380 016403

[info@vadatech.com](mailto:info@vadatech.com) | [www.vadatech.com](http://www.vadatech.com)

# Choose VadaTech

## We are technology leaders

- First-to-market silicon
- Constant innovation
- Open systems expertise

## We commit to our customers

- Partnerships power innovation
- Collaborative approach
- Mutual success

## We deliver complexity

- Complete signal chain
- System management
- Configurable solutions

## We manufacture in-house

- Agile production
- Accelerated deployment
- AS9100 accredited



**vadatech**  
THE POWER OF VISION

## Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

© 2023 VadaTech Incorporated. All rights reserved.  
DOC NO. 4FM737-12 REV 01 | VERSION 1.6 – MAY/25